






**Art. No: Various**

**An appreciated tool  
 for rational construction  
 and increased security.**

-  The jointed steps are always leveled no matter how the stairs are leaning.
-  Non-slip steps of expanded sheet metal prevents slipping accidents.
-  Jointable handrail with intermediate can mounted on any side or on both sides.
-  Sharpened side rails prevent slipping on the surface.
-  Can be unlimited jointed. Simple joint assembly and support available for heights greater than 3.5 m.
-  Manual locking device locks the stairs into the desired tilt angle.
-  Hot dip galvanized.
-  Applications:
  - Buildings and barracks/cabins • Slopes and shaft pits • Industries and plants (temporary and permanent)
  - Crushers and mobile machines and more ...



**For assembly instructions etc. see user manual.**

## Technical data.

Art. No	Weight	Art No:	Weight
Stairs	Stairs	Handrail	Handrail
HP1004	3-steps 0-75cm	17 kg	HP1009 5,3 kg
HP1003	6-steps 0-150cm	31 kg	HP1008 7,6 kg
HP1002	9-steps 0-225cm	47 kg	HP1007 10 kg
HP1001	12-steps 0-300cm	57 kg	HP1006 13,7 kg
HP1000	15-steps 0-375cm	82 kg	HP1005 16 kg
HP1018	18-steps 0-450cm	98 kg	HP1019 19,8 kg

- Handrails:** Handrails always on the correct height from the stair regardless of the slope/angle.
- Stair width:** Totalwidth 75 cm.
- Material:** Siderails, handrails made from rectangular high quality steelpipes, treads/steps includes expanded sheet metal.
- Standard:** Complies with EN12811
- Surface treatment:** Hot dip galvanized

15-21 Steps. We recommend to use Universal support HP1023  
 22 Steps and more - Combibeam HP1015/HP1016 must be used.

