

Art. No: **HP21300**

Galvanized props with internal thread for heights between 170 cm to 300 cm. A piston that is slightly lighter and can withstand up to 35 kN load.

The prop has a covered thread that prevents concrete spillage from making it sluggish. Works as a housing prop or industrial prop.



Height: 1,7-3,0m.



Manufactured by: Altrad.



Hot dip galvanized.



Loads: 18-35kn



Protected / built in treads to ensure friction free use.



Weight: 15,4kg



The props is adjustable and different load classes apply at different working heights. See the load table for the permissible load class per working height on this prop on the next page.

Against quotations we can offer props in other dimensions and load classes.

Unit weight	15,4kg
Name	A300
3.0	18.0
2.9	20.0
2.8	21.5
2.7	23.0
2.6	25.0
2.5	26.5
2.4	28.0
2.3	30.0
2.2	31.5
2.1	33.0
2.0	35.0
1.9	35.0
1.8	35.0

Work height (m)

Maximum load (kN)

Permissible loads in kN. Indications are that the stamp is used in accordance with the supplier's installation instructions. The load must come down centrally in the prop. The prop must be secured against horizontal movements in the lower and upper edges.

The props is delivered with advantage in our galvanized steel baskets with space for 50 props, Art no: HP22800

See prop-accessories for all necessary parts.